



RESIDUAL POWER PERCENTAGE (Cable Run Efficiency)

Given a power fed to the X value (any value expressed in Watts), the actual power output of the cable is shown in the table in the form of remaining percentage. (for example, if we use a cable such as M&P-ULTRAFLEX 7, entering 1000 Watts over a length of 35m, at a frequency of 144 MHz, there remains 57,2% of 1000). **For maximum applicable power, see the Power Handling of the cable concerned.** From these values, have already been deducted the SRL values, typical of each one of our models, for the respective frequencies.

REMEMBER: Make sure to match the line accurately!

		M&P-ULTRAFLEX 7 / .287"													
feet		16,4	32,8	49,2	65,6	82	114,8	164	246	328	426,5	524,9	656,2	984,2	
meters		5	10	15	20	25	35	50	75	100	130	160	200	300	
Wave length	MHz	Useful signal output (residual power %)													
Frequencies	85.71 m	3,5	98,4	97,0	95,6	94,2	92,8	90,1	86,2	80,1	74,4	68,1	62,3	55,4	41,2
	42.85 m	7	98,1	96,3	94,5	92,8	91,1	87,8	83,1	75,8	69,1	61,8	55,4	47,8	33,0
	21.42 m	14	97,4	95,0	92,6	90,3	88,0	83,7	77,5	68,3	60,2	51,7	44,4	36,2	21,8
	10.71 m	28	96,5	93,2	90,1	87,0	84,0	78,4	70,7	59,5	50,0	40,6	33,0	25,0	12,5
	6 m	50	95,4	91,1	87,0	83,1	79,3	72,3	63,0	50,0	39,7	30,1	22,8	15,7	6,2
	2.08 m	144	92,3	85,2	78,7	72,7	67,1	57,2	45,1	30,3	20,3	12,6	7,8	4,1	
	69 cm	430	86,6	75,2	65,2	56,6	49,1	37,0	24,1	11,8	5,7				
	23.1 cm	1296	76,7	59,2	45,6	35,1	27,0	15,9	7,0						
	12.5 cm	2400	67,4	45,9	31,2	21,0	14,0	5,8							
	10 cm	3000	64,3	41,9	27,1	17,3	10,9	3,8							
	7.5 cm	4000	59,2	35,4	20,9	12,0	6,6								
	6 cm	5000	53,5	28,9	15,0	7,1									
	5 cm	6000	48,9	24,0	10,8	3,8									

M&P-ULTRAFLEX 7 / .287" Power Handling/Temperature (in Continuous Carrier)

		Temperature C° / F°										
Wave length	MHz	-10 / 14	-5 / 23	0 / 32	10 / 50	20 / 68	30 / 86	40 / 104	50 / 122	60 / 140	70 / 158	
Frequencies	166.66 m	1,8	6838	6838	6638	6217	5724	5138	4572	3900	3228	2560
	85.71 m	3,5	5252	5076	4927	4614	4248	3814	3393	2894	2395	1900
	42.85 m	7	4202	4061	3941	3692	3398	3051	2714	2315	1916	1520
	30 m	10	3538	3420	3319	3109	2862	2569	2286	1950	1614	1280
	21.42 m	14	3056	2953	2866	2685	2472	2219	1974	1684	1394	1105
	14.28 m	21	2586	2499	2425	2272	2091	1878	1670	1425	1179	935
	10.71 m	28	2241	2166	2102	1969	1812	1627	1448	1235	1022	811
	6 m	50	1681	1624	1577	1477	1359	1220	1086	926	767	608
	3 m	100	1159	1120	1087	1018	937	842	749	639	529	419
	2.08 m	144	974	942	914	856	788	707	629	537	444	352
	1.5 m	200	820	792	769	720	663	595	530	452	374	297
	75 cm	400	570	551	534	501	461	414	368	314	260	206
	69 cm	430	547	528	513	480	442	397	353	301	249	198
	37.5 cm	800	393	380	369	345	318	285	254	217	179	142
	30 cm	1000	348	337	327	306	282	253	225	192	159	126
	23.1 cm	1296	301	291	283	265	244	219	195	166	137	109
	12.5 cm	2400	208	201	195	183	168	151	134	115	95	75
10 cm	3000	186	179	174	163	150	135	120	102	85	67	
7.5 cm	4000	158	153	148	139	128	115	102	87	72	57	
6 cm	5000	136	132	128	120	110	99	88	75	62	49	
5 cm	6000	122	117	114	107	98	88	79	67	55	44	
4.2 cm	7000	109	105	102	96	88	79	71	60	50	39	
3.75 cm	8000	98	95	92	86	79	71	63	54	45	36	

Do not use the cable as power supply for both direct current and 50-60 HZ mains